



massimo sfilo idraulico / max. hydraulic outreach / max. alcance hidraulico / rallonge hydraulique max. / max. hydraulische reichweite	5.25 m	
minimo sfilo idraulico / min. hydraulic outreach / min. alcance hidraulico / rallonge hydraulique min. / min. hydraulische reichweite	3.05 m	
altezza massima / max height above installation level / altura max. desde el filo infer. de la base / hauteur de levage au dessus du plan de pose / hubhöhe ab fahrzeugrahmen	6.63 m	
portate gru base / outreach - lifting capacity / alcances hidraulicos - capacidad / extention - charge / hydraulische reichweite - hubkraft	3.05 m	710 kg
	4.15 m	490 kg
	5.25 m	370 kg
portata prolunga manuale / outreach with manual extens. - lifting capacity / alcances con prolongas manuales - capacidad / extention avec rallonges manuelles - charge / reichweite mit manuellen verlängerungen - hubkraft	6.35 m	250 kg
portata pompa consigliata / recommended pump delivery / caudal bomba aconsejada / debit d'huile recommandé / förderleistung der hydraulikpumpe	10 l/min	
pressione di lavoro / working pressure / presión de trabajo / pression de travail / betriebsdruck	230 bar	
capacità serbatoio / tank capacity / contenance du reservoir / capacidad deposito de aceite / inhalt des öltanks	30 l	
angolo di rotazione / slewing angle / angulo de giro / angle de rotation / schwenkbereich	402°	
coppia di rotazione / slewing torque / momento de giro / couple de rotation / drehmoment	2.8 kNm	
altezza a riposo / height in folded position / hauteur en position repliee / altura en posición de reposo / höhe ab fahrzeugrahmen zusammengelegt	1485 mm	
larghezza a riposo / width in folded position / largeur en position repliee / anchura en posición de reposo / breite zusammengelegt	1800 mm	
peso gru completa di stabilizzatori estensibili e martinetti piedi / crane weight including side extensions and rams of stabilizers / peso de la grua incluidos las extensiones y los cilindros de los estabilizadores / poids grue complète de bequilles extensibles et verins stabilisateurs / Eigengewicht, einschl-manuell seitlich ausziehbare Abstützungen	335	

- - - - - AREA DI LAVORO \ WORKING AREA
 ——— PORTATA CON LIMITATORE DI MOMENTO \ LIFT WITH LOAD LIMIT VALVE
 ——— PORTATA PROLUNGHE MANUALI \ MANUAL EXTENSIONS LIFT

Ing. BONFIGLIOLI S.p.A. BOLOGNA - ITALIA

tel 051/6867214 fax 051/6867222 e-mail: cranes@ingbonfiglioli.it